



27-10 HUNTERS POINT AVE.
(49TH AVE.)
LONG ISLAND CITY
NEW YORK 11101-4498

TEL. (718) 784-7330
1-(800) 660-7330
FAX. (718) 392-8283

SALES@BLACKBEAROIL.COM
TECHNICAL@BLACKBEAROIL.COM
LUBRICANTS@BLACKBEAROIL.COM
FAX@BLACKBEAROIL.COM

BLACK BEAR UTF - Universal Tractor Fluid

OVERVIEW

It is a premium, exceptional high quality universal tractor hydraulic fluid for use in transmissions, final drives and hydraulic systems of all major brands of tractors and other farm equipment using a common fluid reservoir. This fluid incorporates the latest additive chemistry to provide maximum protection for all systems requiring a universal fluid.

FEATURES & BENEFITS

Enhanced frictional properties that optimize clutch and PTO performance and improve wet brakes and PTO chatter control. (Power Take-Off)

Compatible with latest clutch materials and elastomers resulting in longer clutch life and reduced leakage. High viscosity index and shear stability causing consistent operating response.

Excellent protection against rust, corrosion, yellow metal etching, low temperature properties, strong anti-wear, extreme pressure properties, thermal and oxidation stability.

Multipurpose capability in simplifying inventory by reducing misapplication problems.

APPLICATIONS

Heavy duty transmissions, differentials, final drives, hydraulic systems, power steering systems, wet brakes, PTO's and hydrostatic drives. Top-up and re-fill of systems. Commercial transmission applications requiring Type A (Suffix A), Dexon and Type F fluids. Do not use in passenger car automatic transmissions.

SPECIFICATIONS

AGCO, Deutz-Allis-White: Power Fluid 821-XL Case, Case IH: HyTran Plus, Spec. MS-1207; Hy-Tran Ultra, MS-1208 J.Deere: Hy-Guard, Spec. JDM J20C Hesston Fiat (tractors): OlioFiat Tutela Multi-F Kubota: Super UDT Fluid Landini, Massey Ferguson: Permatran-III, M1135, M1143, M1144 New Holland, Ford: 134 Hydraulic Fluid, Spec. ESN M2C134-D

TYPICAL PROPERTIES

PRODUCT CODE	4412-055
---------------------	-----------------

Viscosity, cSt @ 40°C	59.5
-----------------------	------

Viscosity, cSt @ 100°C	9.25
------------------------	------

Viscosity, cP @ -20°C	4500
-----------------------	------

Viscosity, cP @ -35°C	49000
-----------------------	-------

Viscosity Index	150
-----------------	-----

Pour Point, °F	-44
----------------	-----

Flash Point, °F	432
-----------------	-----

Sulfated Ash, wt%	1.48
-------------------	------

Total Base Number	10.1
-------------------	------

Zinc, wt%	0.157
-----------	-------