



27-10 HUNTERS POINT AVE.
(49TH AVE.)
LONG ISLAND CITY
NEW YORK 11101-4498

TEL. (718) 784-7330
1-(800) 660-7330
FAX. (718) 392-8283

SALES@BLACKBEAROIL.COM
TECHNICAL@BLACKBEAROIL.COM
LUBRICANTS@BLACKBEAROIL.COM
FAX@BLACKBEAROIL.COM

BLACK BEAR 75W90 FULL SYNTHETIC GL-5

OVERVIEW

BLACK BEAR 75W90 FULL SYNTHETIC GL-5 is a full synthetic, premium quality, commercial drive-train lubricant designed to meet the rigorous demands of extended drain warranty requirements. It provides outstanding performance in heavy duty drive-trains where extreme pressure and shock loading are common. Formulated for extreme cleanliness and superior thermal stability under severe conditions, this oil also offers enhanced friction reduction properties and exceptional shear stability.

FEATURES & BENEFITS

- Exceptional thermal stability
- Resistance to high temperature oxidation
- Extend gear and bearing life to minimum deposits and longer seal life.
- Outstanding protection against low speed/high torque-wear and high speed scoring.
- Retains viscosity and film strength under severe operating conditions
- Exceptional shear-stability.
- Compatible with typical automotive seals and gaskets
- Excellent rust, staining, and corrosion protection of copper and its alloys.

APPLICATIONS

- Heavy-duty manual transmissions, axles and final drives requiring API GL-5 and MT-1 performance.
- Off-highway light and heavy-duty trucks, busses and vans.
- Includes hypoid and worm gears operating under conditions where high speed/high torque conditions prevail.
- Equipment such as winch reduction gears and crawler vehicle propulsion gear drives that are exposed to severe low temperatures.

SPECIFICATIONS

- Eaton Roadranger (E500)
- ArvinMeritor extended warranties of 750,000 miles with oil drains of 500,000 miles.
- Mack GO-J and GO-J Plus (75W90) extended service classifications.

TYPICAL PROPERTIES

PRODUCT CODE	6332
SAE Grade	75W-90
Viscosity, cSt @ 100°C	15.0
Viscosity, cSt @ 40°C	101
Pour Point, °C	-38
Flash Point, °C	205
Density @ 15C	0.866
Foam Sequence I, II, II D892	Pass