



27-10 HUNTERS POINT AVE.
(49TH AVE.)
LONG ISLAND CITY
NEW YORK 11101-4498

TEL. (718) 784-7330
1-(800) 660-7330
FAX. (718) 392-8283

SALES@BLACKBEAROIL.COM
TECHNICAL@BLACKBEAROIL.COM
LUBRICANTS@BLACKBEAROIL.COM
FAX@BLACKBEAROIL.COM

BLACK BEAR 80W140 FULL SYNTHETIC GL-5

OVERVIEW

BLACK BEAR 80W140 FULL SYNTHETIC GL-5 is a full synthetic, premium quality, commercial drivetrain lubricant designed to meet the rigorous demands of extended drain warranty requirements. It provides outstanding performance in heavy duty drivetrains where extreme pressure and shock loading are common. Formulated for extreme cleanliness and superior thermal stability under severe conditions, this oil also offers enhanced friction reduction properties and exceptional shear stability.

FEATURES & BENEFITS

- Extended drain interval
- Excellent EP properties
- Superior thermal stability
- Exceptional Shear stability

SPECIFICATIONS

API GL-5 / MT-1
Scania STO 1:0
Eaton Roadranger (E500)
Mack GO-J plus
Mack GO-J
ArvinMeritor O-76N
International TMS-6816
SAE J2360
MIL-PRF-2105E

TYPICAL PROPERTIES

PRODUCT CODE	6342
SAE Grade	80W-140
Viscosity, cSt @ 100°C	26
Viscosity, cSt @ 40°C	225
Pour Point, °C	-36
Flash Point, °C	210
Density @ 15C	0.870
Foam Sequence I, II, II D892	Pass