



27-10 HUNTERS POINT AVE.  
(49TH AVE.)  
LONG ISLAND CITY  
NEW YORK 11101-4498

TEL. (718) 784-7330  
1-(800) 660-7330  
FAX. (718) 392-8283

SALES@BLACKBEAROIL.COM  
TECHNICAL@BLACKBEAROIL.COM  
LUBRICANTS@BLACKBEAROIL.COM  
FAX@BLACKBEAROIL.COM

## MP No. 2 GREASE

### OVERVIEW

Black Bear MP NO 2 Grease is a high temperature, smooth textured, tacky grease fortified with the latest Sulfur Phosphorous extreme pressure additive and a water resisting co-polymer. Formulated from the highest quality severely hydrotreated base oils in a complex soap thickener, this purple-dyed lubricant has exceptionally high dropping point along with excellent resistance to thermal degradation. When exposed to extreme heat near its dropping point, Black Bear MP No. 2 Grease will return quickly to its normal grease-like consistency. Only a few types of greases have this property. Increased corrosion protection and oxidation under extreme conditions.

### FEATURES & BENEFITS

- Extended bearing life
- Excellent thermal properties
- Provides greater wash off
- Increased corrosion and oxidation protection

### APPLICATIONS

Various automotive parts including chassis, ball joints and wheel bearing  
Wide industrial applications calling for Extreme pressure greases

### SPECIFICATIONS

Meets SAE J310 (3-80), specification for EP (extreme pressure) and multipurpose grease, FMC HD EP GREASE, MACK MG-C and NLGI GC-LB.

### TYPICAL PROPERTIES

Specifications	Characteristics
NLGI Grade	2
Texture	Smooth Tacky
Color	Purple
Dropping Point, F	500+
Water Spray Off, @ 100F SUS	45
4 Ball EP Test, Weld Point, Kg	320
NLGO Category	GC-Lb