



27-10 HUNTERS POINT AVE.
(49TH AVE.)
LONG ISLAND CITY
NEW YORK 11101-4498

TEL. (718) 784-7330
1-(800) 660-7330
FAX. (718) 392-8283

SALES@BLACKBEAROIL.COM
TECHNICAL@BLACKBEAROIL.COM
LUBRICANTS@BLACKBEAROIL.COM
FAX@BLACKBEAROIL.COM

BLACK BEAR NO. 9800 GREASE

OVERVIEW

BLACK BEAR NO. 9800 is an unusually effective tacky multipurpose type grease with water resistant and heat resistant characteristics. Its extreme pressure chemistry is reinforced with a generous amount of Technical Grade Molybdenum Disulfide--a lubricant powder which prevents metal-to-metal contact if the grease film should break down or run dry. Where longer trouble-free bushing and bearing life is desired, BLACK BEAR NO. 9800 is an outstanding performer. This excellent grease is also recommended for wheelbearings--especially for disc brake wheelbearings where the high temperature GM 9985254 grease requirement is specified.

SPECIFICATIONS

Black bear no. 9800 " moly" grease meets and exceeds the following specifications: blaw-knox high temperature grease bucyrus-erie (sd 4711) j. l. Case mpgm caterpillar mpgm fmc hd ep grease gm no. 9985254 high temperature grease international harvester 251 hep mack mg-c sae j310 mar 83: eli (extended lubrication interval) grease multipurpose grease ep (extreme pressure) grease.

TYPICAL PROPERTIES

Grade	Medium light no.
Nlgi	2
Worked penetration @ 77° f. Dropping	265 -295
point, °f., min. Texture	500+
Mineral oil vis. @ 100° f.	Smooth/tacky 800