



27-10 HUNTERS POINT AVE.
(49TH AVE.)
LONG ISLAND CITY
NEW YORK 11101-4498

TEL. (718) 784-7330
1-(800) 660-7330
FAX. (718) 392-8283

SALES@BLACKBEAROIL.COM
TECHNICAL@BLACKBEAROIL.COM
LUBRICANTS@BLACKBEAROIL.COM
FAX@BLACKBEAROIL.COM

BLACK BEAR UNI-SYN LV DEX VI ATF

OVERVIEW

BLACK BEAR UNI-SYN LV DEX VI ATF is a specifically designed, fully synthetic, next generation fluid for use in General Motors vehicles where Dexron VI is specified, as well as most other ATF applications (check your viscosity requirements). Formulated for use in low viscosity ATF applications (Mercon LV, SP; Toyota WS, etc.) and designed for the latest six and seven speed automatic transmissions.

FEATURES & BENEFITS

- Extended fluid life
- Improved oxidation and thermal stability
- Optimized frictional properties that provide smooth gear shifting during low temperature operation and help prevent transmission vibration.
- Outstanding low temperature performance.
- Improved anti-wear protection which contributes to extended transmission life.
- Outstanding resistance against sludge and deposit formation.

APPLICATIONS

BLACK BEAR UNI-SYN LV DEX VI ATF is also completely backward compatible for use in older GM vehicles that specify Dexron III H, Dexron IIIG, Dexron IID, Dexron II or Dexron fluids. This fluid has shown outstanding performance in friction durability, shear and oxidation stability and provides longer service life with superior foam resistance, minimization of deposits and consistent shift performance.

TYPICAL PROPERTIES

PRODUCT CODE	5162
	Dex VI ATF
Density, @ 15°C	.844
Flash Point, COC °C	191
Viscosity, Cst @ 40°C	29.8
Viscosity, Cst @ 100°C	5.98
Viscosity Index	152
Viscosity, cP @ -40°C	11500
Pour Point, °C	-50
Phosphorous, %wt.	.0194