



27-10 HUNTERS POINT AVE.
(49TH AVE.)
LONG ISLAND CITY
NEW YORK 11101-4498

TEL. (718) 784-7330
1-(800) 660-7330
FAX. (718) 392-8283

SALES@BLACKBEAROIL.COM
TECHNICAL@BLACKBEAROIL.COM
LUBRICANTS@BLACKBEAROIL.COM
FAX@BLACKBEAROIL.COM

BLACK BEAR EPX 85W140 GEAR LUBE GL-5

OVERVIEW

BLACK BEAR EPX 85W140 GEAR LUBE GL-5 are multipurpose, extreme pressure gear lubricants which are recommended for hypoid and bevel gear sets used in many front and rear drive differentials. These gear oils are intended for service fill, top-off and refill of hypoid and other drive axles which recommend API GL-5 gear lubricants. Can be used as a top off in limited slip applications, but is not a limited slip capable product intended for fill or refill.

FEATURES & BENEFITS

- Excellent EP properties
- Meets all GL-5 requirements
- Can be used for refill, top-off, and initial fill, depending on application

APPLICATIONS

BLACK BEAR EPX 85W140 GEAR LUBE GL-5 are suitable for use in manual transmissions where a GL-5 gear lubricant is recommended. Meet or exceed API GL-5, API MT-1, MIL-PRF-2105E, Ford WSP-M2C197-A, Meritor Automotive 0-76-D, Navistar B-22, PG-2 (anticipated requirements) and Mack GO-J, depending on viscosity

TYPICAL PROPERTIES

PRODUCT CODES	6062
SAE Grade	85W-140
AGMA no.	7EP
Viscosity, cSt/40 °C	451.25
Viscosity, cSt/100 °C	29.55
Viscosity Index	98
API Gravity	27.5
Flash Point, COC °F	460
Pour Point, °C	0
Oxidation Stability	5.7
Demulsibility, total free water, ml	85.5
Emulsion, ml	Nil
Rust Test	Pass
Copper Strip, Class	1
Foam Test	TR/0